

products > Engine oils for cars and transporters > Synthetic engine oil > FANFARO 6719 5W-30



FANFARO 6719 5W-30

Universal premium synthese engine oil (contains PAO) for modern gasoline and diesel engines of VW group cars (including direct injection) with and without turbocharging, including those equipped with pump-injectors (Pumpe-Duse).

Product properties:

- Due to the special friction modifiers contained, it has excellent anti-wear, extreme pressure, and anti-friction properties, which ensures long and trouble-free operation of the pump-nozzle system and the entire gas distribution mechanism, reducing cam wear;
- Due to its excellent detergent-dispersing properties and high thermal-oxidative stability, it effectively combats all types of deposits and keeps engine parts clean throughout the entire interval between replacements;
- Saves fuel due to optimal anti-friction properties;
- Synthetic base provides a low solidification temperature (- 45 °C and below) and guarantees easy low-temperature engine start-up due to exceptional turn ability and pump ability, which significantly reduces engine starting wear.
- It has optimal viscosity over a wide temperature range, which ensures stable operation in all operating modes, including in urban mode and under overload conditions;
- Due to its high thermal-oxidative stability, it effectively resists aging;
- Compatible with all exhaust gas neutralization systems, DPF, TWC, EGR and SCR through the use of Mid SAPS technology;
- Used in engines with extended oil change intervals (Long Life up to 30,000 km) and conventional;
- Suitable for engines running on liquefied natural gas (LNG) and petroleum gas (LPG).

Designed for gasoline and diesel engines of EURO IV and EURO V wide fleet of vehicles (cars, light SUVs, vans and light trucks) of VW imposes additional requirements on motor oils in accordance with the specifications 504 00/507 00 and previous.

The oil is not suitable for use in heavy trucks and similar vehicles!

CORRESPONDS WITH REQUIREMENTS / SPECIFICATIONS / PRODUCTS:

Specifications:

SAE 5W-30

API SN
ACEA C3
BMW Longlife-04
MB 229.51
PORSCHE C30
VOLKSWAGEN TL 52195

Approval:

VOLKSWAGEN 504 00 Approval
VOLKSWAGEN 507 00 Approval

PACKAGES (ARTICLE NUMBER):

5L (FF6719-5)
1000L (FF6719-IBC)
208L (FF6719-DR)
60L (FF6719-60)
20L (FF6719-20)
10L (FF6719-10)
1L (FF6719-1)