

products > Industrial and marine oils > Hydraulic oils > FANFARO HYDRO HV ISO 46 LONGLIFE



FANFARO HYDRO HV ISO 46 LONGLIFE 2202

All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product properties:

- It contains antiwear, anti-oxidising, anticorrosion and antifoaming additives.
- It has good antiwear properties that minimise the wear of the parts related to hydraulic pumps thus ensuring their long service life;
- Modern cleaning-dispersing additives ensure an ideal cleanliness of hydraulic system parts thus also protecting precision pairs from wear and extend the equipment life;
- A high thermo-oxidative and thermal stability reduce the formation of all types of deposits and corrosive substances that increase the reliability of subsystems' operability (valves, hydraulic directional valves, etc.) and simultaneously distinguishes itself by an excellent filtering ability;
- Due to good anticorrosion properties, it protects surfaces of all used metals and alloys against a corrosive impact of acids and water that significantly reduce the maintenance and repairs costs;
- It is characterised by excellent demulsifying properties, a low freezing temperature and a long service life;
- The resistance to foam formation enhances the efficiency of hydraulic pumps;
- It is neutral in regards to all sealing materials and paint-and-lacquer coatings compatible with mineral oils. It prevents leakages thus reducing buying costs.

It is recommended to be used as a power fluid for industrial hydraulic systems:

- Stationary equipment (pressing machines, elevators, moulding machines, robots, industrial machines, forming machines, etc.);
- Mobile equipment (construction, highway, mining, tree harvesting, various municipal and special equipment, etc.);
- The following types: DENISON, EATON VICKERS, GEROTOR, GRESEN,

HPM, CESSNA, HYDRECO, WORTHINGTON, etc.

- Where there are syringe, geared, impeller, axial piston pumps in compliance with manufacturer's requirements;

- When the oil standards DIN 51524 Part 2 (HLP) or ISO 11158 (HM) are required to be used.

In order to properly use it, thoroughly read the user's manual of the equipment!

CORRESPONDS WITH REQUIREMENTS / SPECIFICATIONS / PRODUCTS:

Specifications:

SAE MS 1004

ISO Viscosity Grade 46

DIN 51524-2 (HM)

DIN 51524-3 (HVLP)

ISO 11158 (HM, HV, HVLP)

Recommendation:

ASTM USA D6158

ANSI AGMA 9005-E02-RO

AIST 126

AIST 127

JCMAS P041 HK Hydraulic specification

GERMAN STEEL INDUSTRY SEB 181222

BOSCH REXROTH RE 90220

EATON M-2950-S

EATON I-286-S3

GM LS2

MAG CINCINNATI P-68

MAG CINCINNATI P-69

MAG CINCINNATI P-70

PARKER DENISON HF-0

PARKER DENISON HF-1

PARKER DENISON HF-2

SPERRY VICKERS M-2950-S

SPERRY VICKERS I-286-S3

PACKAGES (ARTICLE NUMBER):

208L (FF2202-DR)

1000L (FF2202-IBC)

20L (FF2202-20)