

products > Engine oils for trucks & buses > Synthetic engine oil > FANFARO TRD-23 UHPD 5W-30



FANFARO TRD-23 UHPD 5W-30 6123

Innovative energy-saving synthetic (contains PAO) low-viscosity engine oil developed for the latest generation of turbocharged diesel engines operating under severe conditions, using ultra-low sulphur fuel (15 ppm or less) and equipped with exhaust gas aftertreatment systems: SCR, EGR and DPF. Provides engine protection in accordance with EPA 2010 and GHG 17. Developed to meet the requirements of Volvo and Daimler.

Product properties:

- Improves fuel economy (up to 0.5 % compared to 10W-30 oils and up to 1.3 % compared to 15W-40 oils) and has extended change interval due to increased shear stability and very low volatility;
- The unique low-viscosity synthetic base of the highest quality, combined with a unique additive package and viscosity modifiers, provides an increased viscosity index and unrivalled anti-friction, anti-wear and anti-scuffing properties, which significantly extends the service life of machinery in all, even the most extreme, operating modes in a wide enough range of ambient temperatures and provides unrivalled shear stability;
- The synthetic base, special surfactants and TBN-busters give the oil increased thermal oxidation stability, excellent detergent-dispersing properties and low ash content, which effectively reduces carbon and lacquer formation, prevents the formation of deposits of all kinds and keeps engine separate parts, especially the cylinder-piston group, perfectly clean throughout the entire interval between changes;
- Due to a low viscosity PAO-containing base it has excellent low-temperature properties, including a low pour point, which provides excellent oil pumpability and engine components turnability at low temperatures, easy "cold start" (down to -45 °C) and reduced starting wear;
- Effectively protects engine separate parts from all types of corrosion;
- Effectively prevents the increase of shear force during operation caused by viscosity increase due to soot dispersion;
- Maintains the efficiency of exhaust gas aftertreatment systems over a long period of time, extends their service life and reduces losses caused by clogging of diesel particulate filters (DPF).

Designed for engines of 2021 and later versions installed in on-road (long-

haul tractors, buses, etc.), off-road (construction, mining, agricultural) and special-purpose vehicles of European, American and Asian manufacturers meeting Euro VI and EPA 10 requirements where API FA-4 performance level is required. Oils of this category are not interchangeable and backwards compatible with oils of CK-4 category and its predecessors. Can be used in light diesel engines and in diesel engines without diesel particulate filters (DPF).

CORRESPONDS WITH REQUIREMENTS / SPECIFICATIONS / PRODUCTS:

Specifications:

SAE 5W-30
API CK-4
JASO DH-2
JASO DH-1
JASO DL-0
MAN M 3777
MAN M 3775
ACEA E4-22
ACEA E7-22
ACEA E11-22
DAIMLER DTFR 15C120
MB 228.51
MB 228.31
MAN M 3677
MAN M 3477
MAN M 3271-1
SCANIA LDF-4
MTU Category 3.1 and Category 2.1
VOLVO VDS-4.5
MACK EOS-4.5
RENAULT RLD-4
CATERPILLAR ECF-3
CUMMINS CES 20086
CUMMINS CES 20081
DETROIT DIESEL DFS 93K222
DETROIT DIESEL DFS 93K218
DAF Extender Drain
ACEA E8-22

PACKAGES (ARTICLE NUMBER):

208L (FF6123-DR)
20L (FF6123-20)
1000L (FF6123-IBC)