

products > Engine oils for trucks & buses > Multigrade engine oil > FANFARO Ultra Mix 25W-60



FANFARO ULTRA MIX 25W-60 6408

Special high-viscosity high-alloy mineral engine oil for modern high-load and high-speed diesel engines with and without turbocharging, operating at high loads and high ambient temperatures (+ 50° C and above), including for engines with high mileage (120 000 km or more). Designed specifically to provide maximum protection of engines from carbon deposits and deposits of all kinds and get the most out of them under extreme loads, while extending their service life.

Product Properties:

- Effectively resists thermal degradation, while maintaining the desired viscosity at extreme operating temperatures of the engine;
- High-viscosity mineral base of the highest quality provides excellent anti-friction and anti-wear properties at extreme ambient temperatures, which significantly extends the life of engines compared to their analogues;
- In comparison with analogues, it has increased thermal-oxidative stability and low precipitation, which, combined with excellent detergent-dispersing properties (TBN >10), effectively reduces carbon and varnish formation, prevents the formation of deposits of all types and keeps engine parts clean throughout the entire interval between replacements;
- A unique dispersant additives to effectively maintain the soot particles in suspension;
- Perfectly compatible with all types of seals, and thanks to its high-viscosity base, it has a low tendency to leak even when they are worn out;
- Contains components that prevent oxidation and deposition of dirt on the pistons and rings, is completely removed from the cylinder walls by oil-removing rings, which, combined with low evaporation, significantly reduces oil consumption "on fumes" even on heavily worn engines;
- The use of non-destructive thickening additives of the latest generation allows you to maintain the required viscosity during the entire interval between replacements;
- Effectively protects engine parts from all types of corrosion;
- Can be used when working on fuel with high sulfur content.

It is intended for all types of high-load diesel engines of highway (mainline tractors, buses, etc.), off-road (construction, mining, agricultural) and special equipment of European, American and Asian manufacturers that meet the requirements of Euro I, II, III, IV where the level of performance

properties CF-4 or lower is required.

Specifications:

SAE 25W-60

API CF-4

PACKAGES (ARTICLE NUMBER):

5L (FF6408-5)

20L (FF6408-20)